

# Tentative Rules for 2025 Season

## Muscle Tractors (Farm Stock)

### 9,000lb (Naturally Aspirated)

- Class limited to a 6 cylinder naturally aspirated engine or a 2 or 4 cylinder engine with a turbo.
- Max tire size 18.4x38 (Top Cut or Uncut)
- Speeds will be 6 and 8mph
- 3,000 RPM limit

### 9,000lb, 11,500lb, 13,000lb

- Primary speeds are 8 and 14mph
- 6mph & 12mph will be available dependent on promoter choice.
- Turbos are allowed
- Max tire size for 9,000lb is 18.4x38 (Uncut or Top Cut)
- Max tire size for 11,500lb and 13,000lb is 20.8 x 38 (Uncut or Top Cut)
- All Farm Stocks must have PTO and Rock Shaft
- Hitch length is 20" from the center of rear axle
- Weights must not interfere with the hooking of the sled or sled hitch
- Dimension of the pulling hitch is 3" wide x 3.75" long
- Narrow front-ends are allowed.

### 10,000lb Altered Farm

- Open speed limit
- 3,000 RPM limit with sensor
- Max turbo inlet size is 2.75"
- A-Pump only
- Max tire size is 20.8x38 Uncut or Top Cut only
- Cubic inch limit is 504 (540 V8 Masseys are allowed)
- Hitch length is 20" from the center of rear axle
- Dimension of the pulling hitch is 3" wide x 3.75" long

### Street Diesel Trucks (4WD, Duallys are allowed)

- 8,500lbs weight limit
- Engine must match the sheet metal
- Stock turbo
- Trucks may have front weight rackets or hanging weights
- Weight racket maximum is 60" from center of front axle
- Bump stops and traction bars are allowed
- Wheel base must be stock
- No alterations of chassis
- Hitch height is 24"
- No hitch braces further forward than the center of the rear axle
- Tire size is 35" for single and 33" for duallys
- \$500 protest fee for turbo. Turbo is only to be seen by official & truck owner.

- If driver refuses to show turbo, first offense will result in disqualification. Second offense will result in disqualification and suspension from competition for 1 year & a day.

**Work Stock Diesel Trucks** (4WD, Duallys are allowed)

- 8,500lbs weight limit
- Engine must match the sheet metal
- 2.5 max turbo
- Trucks may have front weight rackets or hanging weights
- Weight racket maximum is 60" from center of front axle
- Bump stops and traction bars are allowed
- Wheel base must be stock
- No alterations of chassis
- Hitch height is 24"
- No hitch braces further forward than the center of the rear axle
- Tire size is 35" for single and 33" for duallys
- \$500 protest fee for turbo. Turbo is only to be seen by official & truck owner.
- If driver refuses to show turbo, first offense will result in disqualification. Second offense will result in disqualification and suspension from competition for 1 year & a day.